

Q16 - Engineering Directed Standard Tool/Perishable Tool Inspection Requirements

"IMPORTANT NOTICE: A hard copy of this document may not be the document currently in effect. The current version is always the version on the Lockheed Martin network."

* REVISED

** ADDED

I. APPLICATION

Except as otherwise directed by Buyer, the governing revision of this document shall be the revision in effect on the date of this Purchase Order (PO). Subject to limitation by Buyer, if any, if subsequent revisions of this Buyer document are issued, Seller is authorized to use the latest revision of this document. If Seller opts for use of the latest revision, Seller shall utilize the applicable portions of the latest revision in their entirety.

NOTE: As used herein, the term "Buyer" is synonymous with the term "LOCKHEED MARTIN", the terms "Purchase Order" and "PO" are synonymous with the term "Contract", the terms "Item" and "Items" are synonymous with the term "Work", and the term "Seller" is synonymous with the term "SELLER", all as may be used elsewhere in the PO of which this document "Q16 – Engineering Directed Standard Tool/Perishable Tool Inspection Requirements" is a part.

II. REQUIREMENTS

- A. Seller shall perform an inspection after all normal manufacturing operations have been completed. Seller shall perform this inspection of any Item prior to delivery to Buyer.
- B. Seller shall furnish the results of this inspection and any previous inspections to Buyer or Buyer's Representative upon request.
- C. Seller shall be permitted to perform sample inspection on the Items (reference Paragraph II. A.) as long as one (1) of the following statistically valid sampling plans is used, unless otherwise specified by Buyer in writing.

- *
 - 1. MIL-STD-1916
Note: The sampling tables in MIL-STD-105 can still be used
 - 2. ISO 2859-1
 - 3. NSI/ASQ Z1.4-2003

III. ENGINEERING INSPECTION CRITERIA

- A. Equipment to inspect and/or validate the required characteristics varies based upon the tool type. Seller shall ensure that each piece of inspection equipment is capable of measuring to the tolerance specified in Industry Standard and/or Buyer specifications. Seller shall provide a listing of measuring equipment, gages, holding devices, and method employed for validating each characteristic identified in Paragraph III. C (at the Seller's facility) to Buyer or Buyer's Representative upon request.
- B. Prior to Buyer receipt, Seller shall ensure that all Items delivered shall have the following inspected for conformance to the applicable Buyer's Standard Tool Specification, "P" Sheet, "C" Number Drawing, TMS (Tool Manufacturing Standard), and/or NAS (National Aerospace Standard):
 - 1. Tool number and Dash Number Identification
 - 2. Verification that the tool is obtained from an approved manufacturer (if applicable)
 - 3. Manufacturer's Certification, as required
- C. In addition to the baseline requirements specified in Paragraph III. B, Seller shall inspect each tool category identified below against the respective requirements for each of the Buyer's sites identified in Table 1.

***Table 1 Buyer Inspection Requirements by Tool Category**

| Lockheed Martin Aeronautics | | | | |
|---|---|---|--|---|
| Common Characteristics for Cutting Tools (Except Saws) | Damage Check | End Mills | Radial Rake Angle | |
| | Identification | | Corner Radius | |
| | Material Type | | Radius Mismatch | |
| | Surface Finish/Treatment | | Preset Flats Length/Depth | |
| | Overall Length | | End Concavity | |
| | Flute Length | | Counter-sinks | Countersink Angle |
| | Cutter Diameter | | | Axial Rake Angle |
| | Backtaper | | | Seat Angle |
| | Pilot Diameter (Where Applicable) | | | Thread 2A Fit |
| | Pilot Length (Where Applicable) | | | Countersink/Pilot Radius |
| Helix | Counter-bores | Radial/Axial Rake | | |
| Margin Width | | Corner Radius | | |
| Relief & Clearance Angles | | Flat/Perpendicular Cutting Edges | | |
| Run-Out (Concentricity) | Drill/Countersinks Drill/Countersink/Counterbore (Single Pass Tools) | Countersink Angle | | |
| Shank Diameter | | Countersink Axial Rake Angle | | |
| Hardness (Shank, Adapters) | | Transition Between Countersink and Drill | | |
| Threaded Shank (Integrated or Adapted) | | Radius or Counterbore | | |
| Hex Size, Length, Seat Angle and Thread | | Lip Height Variation | | |
| Key Characteristics | | Chisel Edge Centrality | | |
| Straight Shank Drills | | Lip Height Variance | Web Thickness (W2) | |
| | Chisel Edge Centrality | Alignment of Secondary Cutting Edges | | |
| | Core Diameter (W1) | Key Characteristics Identified by Drawing | | |
| | Web Thickness (W2) | | | |
| | Point Type | | | |
| Threaded Shank Drills | Alignment of Secondary Cutting Edges | Taper-Lok Drills | See Paragraph IV for Verification by Buyer | |
| | Lip Height Variance | | Circular Saw Blades | Arbor Hole |
| | Chisel Edge Centrality | | | Kerf Width |
| | Core Diameter (W1) | | | Number of Teeth |
| | Web Thickness (W2) | | | Magnetic Particle Inspection (per ASTM-E-1444) |
| Point Type | Hole Saws | End Configuration | | |
| Alignment of Secondary Cutting Edges | | Arbor Threads | | |
| Chuckling Reamers | Chamfer Lip Height | Drill & Reamer Bushings | End Configuration | |
| | Chamfer Angle | | Inside Diameter | |
| | Core Diameter | | Outside Diameter | |
| Threaded Reamers | Concentricity (between centers) | Keller Lok Bushings | Length | |
| | Chamfer Lip Height | | Inside Diameter | |
| | Chamfer Angle | | Outside Diameter | |
| | Core Diameter | | Length | |
| Concentricity (between centers) | | | | |

D. Seller shall inspect the following characteristics by Standard Tool Number for the Marietta, Meridian, and Clarksburg facilities for the specific features identified below:

1. 550H006
Hole must be centered with no burrs per Buyer specification
2. 550H007
Dash number must match bushing size per Buyer specification
3. 550H008
Slot dimension = 0.141" +.002"/-.000"
4. 550H203
Surface coating adherence
Dash number location per Buyer specification

IV. TAPER-LOK DRILL AND REAMER VERIFICATION BY BUYER (Applies only to Items shipped by Seller to Marietta, Meridian or Clarksburg)

- A. Seller shall submit a sample quantity of Taper-Lok drills and/or reamers to Buyer for verification. The verification process consists of the Buyer drilling and/or reaming holes to verify conformance to Engineering standards.
- B. Seller shall ship the test samples to Buyer at no increase in Buyer's cost or fee.
- C. Seller shall use the following guidelines to determine the proper quantity to be sent by Seller to Buyer for verification.
 - 1. Two (2) drill or reamers from the first 50 received and one (1) drill or reamer for every additional 50 (or portion of 50).
 - 2. The minimum quantity to be sent will be two (2) and the maximum quantity will be six (6).
- D. Seller shall complete the Tapered Cutter Verification Request form or a Buyer-approved alternate for submitting the samples to Buyer. The form may be accessed at:

<http://www.lockheedmartin.com/us/aeronautics/materialmanagement.html>

Highlight "Quality Requirements" and select "Forms". Seller shall submit an individual form, in triplicate, for each unique tool.
- D. Seller shall contact the buyer of record on the Purchase Order for specific shipping instructions for each sample to be submitted for verification.
- E. If and when Seller receives a completed and approved Tapered Cutter Verification Request form from Buyer, Seller shall ship the remaining quantity to Buyer.
- F. If Buyer has documented a rejection on the Tapered Cutter Verification Request form, Seller may submit additional sample quantities to Buyer for verification. If Buyer documents rejection of the additional sample(s), the entire lot is rejected and is not suitable for use by Buyer.