



- Whisper quiet, rugged, all-weather capability
- Configurable Failsafe behaviors
- Operation via handcontroller and/or full Virtual Cockpit™ GCS
- Hot-swappable payload options for ISR, search & rescue, inspection and agriculture
- Industry-leading image stabilization with vision tracking

HANDCONTROLLER

- For small UAS; fixed wing and VTOL
- Stand-alone, untethered operation
- Secure digital data link
- Windows 8.1 based operating system
- Onboard recording of HD video and stills
- Small ergonomic design with large outdoor readable touchscreen
- Ruggedized and weather resistant
- Lightweight: 2.7 -3.3 lbs.
- Long run time (4 8 hours)

Specifications	
Endurance	Up to 50 minutes with payload
Payload	Multiple, hot-swappable payloads
Range	2-10 km (radio and antenna dependent)
Dimensions	32 x 32 x 7 in (12 x 9 x 7 folded)
Weight	5 lbs. (2,300g) with ION payload
Operating Altitude	10-500 ft AGL (typical)
GCS	touchscreen handcontroller or
	laptop-based Virtual Cockpit

Lockheed Martin
Mission Systems and Training
300 M Street, SE
Washington, D.C. 20003
www.lockheedmartin.com/unmanned

© 2015 Lockheed Martin Corporation PIRA# OWG201504004