

Lockheed Martin Thermal Protection Products Catalog Price List

Effective Date
11/15/2021

Ablative/Insulative Materials (Sprayable and Trowelable)

Material	Type I				Type II		Repair Kits		
	5 Gallons	\$/Gal	\$/Kit	1 Gallon	\$/Gal	1 Gallons	\$/Gal	MA2RK	MA4RK
MA-25	5-100	\$285	\$1,425	1-100	\$285	1-25	\$435	\$335	\$335
	105 +	\$275	\$1,375	101 +	\$275	26 +	\$425		
MI-15	5-100	\$265	\$1,325	1-100	\$265	1-25	\$390	MI2RK	MI5RK
	105 +	\$255	\$1,275	101 +	\$255	26+	\$380	\$230	\$290
								GEN2BDAR (.075")	
							\$430		

Topcoats

MI-15 Topcoat		LWTC-40 Topcoat		LWTC Type II		MI-TCRK Repair Kit	
1 Gallon	\$/Gal	1 Gallon	\$/Gal	1 pint	\$/Kit	2 pints	\$/Kit
1-25	\$495	1 and up	\$465	1 and up	\$275	1 and up	\$250
26+	\$480						

Electrically Conductive Materials

High Temp. Elect. Cond. Topcoat		High Temp. Elect. Cond. Type II	
1 Gallon	\$/Gal	1 pint	\$/Pint
1-50	\$8,710	1 and up	\$1,040
51-100	\$8,610		
101-up	\$8,510		

*** Quantity discounts require delivery within 60 days of order ***

MA-25 Sheet Stock Panels (Price reference \$ per panel)

Panel Dash #ID	MA-25 Type III	MA-25 Type IV	MA-25 Type V
Thickness (in)	MA-25 Only	Kevlar/RTV60	MI-15 Topcoat
Size	(12.0" x 24.0")	(12.0" x 24.0")	(12.0" x 24.0")
-100	\$400	\$525	\$535
-125	\$495	\$630	\$640
-250	\$595	\$720	\$735

MI-15 Sheet Stock Panels (Price reference \$ per panel)

Panel Dash #ID	MI-15 Type III		MI-15 Type V
Thickness (in)	MI-15 Only		MI-15 Topcoat
Size	(12.0" x 24.0")		(12.0" x 24.0")
-100	\$360		\$485
-125	\$410		\$535
-250	\$510		See Below
-750	-----		\$1,890
Size		Geometry - Width	(Length up to 24.0")
-250		Simple - Up to 14.0"	\$567
-250		Simple - 14.1" to 22.0"	\$840
-250		Complex - Up to 14.0"	\$595
-250		Complex - 14.1" to 22.0"	\$880
Size		Geometry - Width	(Length 24.1" up to 48.0")
-250		Simple - Up to 14.0"	\$1,135
-250		Simple - 14.1" to 22.0"	\$1,680
-250		Simple - 22.1" to 44.0"	\$3,360
-250		Complex - Up to 14.0"	\$1,190
-250		Complex - 14.1" to 22.0"	\$1,765
-250		Complex - 22.1" to 44.0"	\$3,530

Note: Panel ID/Thickness is the thickness of the Ablator/Insulation panel (i.e. -125 is 0.125" thick MA or MI)

SLA-220

Max panel size - 15" x 18"

Thickness	0.25 inch	0.40 inch	0.50 inch	0.70 inch
	\$695	\$875	\$985	\$1,430

Max panel size - 24" x 24"

Thickness	0.25 inch
	\$1,365

For Technical Information, contact: Michael McBain at (504) 257-0138 or @ michael.c.mc Bain@lmco.com

For Pricing & Availability, contact: Morrie Voss at (504) 257-1386 or @ morrie.a.voss@lmco.com